

HART DYNAMICS TRIGGER SETTINGS FOR ROLAND TD-8__4/1/05 TE3.2

NOTE: Only highlighted (**grey**) settings need to be altered from factory settings.

PRODUCT	PAD TYPE BASIC				ADVANCED						
		SENS	THOLD	CURV	RMSN	SCAN	RTRG	MASK	XTLK	XSTK	H. ADJ
HART PRO SNARE HH TE3.2®	12A	3	4	LINEAR	6	2.0	4	12	OFF	2	NORMAL
HART PRO KICK HH TE3.2®	K12	9	2	LINEAR	NA	2.0	6	0	30	NA	NA
HART PRO TOM 8" HH TE3.2®	10B	3	4	LINEAR	NA	1.0	4	12	60	NA	NA
HART PRO TOM 10" HH TE3.2®	10B	3	4	LINEAR	NA	1.0	4	12	60	NA	NA
HART PRO TOM 12" HH TE3.2®	12B	3	4	LINEAR	NA	1.0	4	12	60	NA	NA
HART PRO KICK BL TE3.2®	K12	9	2	LINEAR	NA	2.0	6	0	30	NA	NA
HART PRO TOM 8" BL TE3.2®	10B	3	4	LINEAR	NA	1.0	4	12	60	NA	NA
HART PRO TOM 10" BL TE3.2®	10B	3	4	LINEAR	NA	1.0	4	12	60	NA	NA
HART PRO TOM 12" BL TE3.2®	12B	3	4	LINEAR	NA	1.0	4	12	60	NA	NA
ACUPAD IS/IIS/IIST TE3.2®	12A	6	4	LINEAR	6	2.0	4	4	60	2	NORMAL
HMK (HAMMER KICK)	K12	9	3	LINEAR	NA	2.0	4	12	30	NA	NA
ACUPAD BDS/ST TE3.2®	K8	11	3	LINEAR	NA	1.5	5	4	30	NA	NA
9" ECYMBAL II	CY1	10	4	LINEAR	NA	2.5	8	8	50	NA	NA
12" ECYMBAL II	CY1	10	4	LINEAR	NA	2.5	8	8	50	NA	NA
12" ECYMBAL II (choke)	CY1	10	4	LINEAR	NA	2.5	8	8	50	NA	NA
14" ECYMBAL II	CY1	10	4	LINEAR	NA	2.5	8	8	50	NA	NA
14" ECYMBAL II (choke)	CY1	10	4	LINEAR	NA	2.5	8	8	50	NA	NA
16" RIDE ECYMBAL II	CY1	10	2	LINEAR	NA	2.5	8	8	50	NA	NA
12" HH ECYMBAL II	CY1	10	2	LINEAR	NA	2.5	4	8	60	NA	NA
12" ECYMBAL II CHINA	CY1	10	4	LINEAR	NA	2.5	4	8	50	NA	NA
14" ECYMBAL II CHINA	CY1	10	4	LINEAR	NA	2.5	5	8	60	NA	NA
9" ECYMBAL S	CY1	10	4	LINEAR	NA	2.5	8	8	50	NA	NA
12" ECYMBAL S	CY1	10	4	LINEAR	NA	2.5	8	8	50	NA	NA
12" ECYMBAL S /CHOKE	CY1	10	4	LINEAR	NA	2.5	8	8	50	NA	NA
14" ECYMBAL S	CY1	10	4	LINEAR	NA	2.5	8	8	50	NA	NA
14" ECYMBAL S /CHOKE	CY1	10	4	LINEAR	NA	2.5	8	8	50	NA	NA
12" ECYMBAL S HH	CY1	10	2	LINEAR	NA	2.5	4	8	60	NA	NA
16" ECYMBAL S RIDE	CY1	10	2	LINEAR	NA	2.5	8	8	50	NA	NA
12" ECYMBAL S CHINA	CY1	10	4	LINEAR	NA	2.5	8	8	50	NA	NA
14" ECYMBAL S CHINA	CY1	10	4	LINEAR	NA	2.5	8	8	50	NA	NA
HM6MT (MULTIPAD)	10B	6	3	LINEAR	NA	1.0	4	4	80	NA	NA
HM1-C (HAMMER PAD)	10B	8	3	LINEAR	NA	1.0	4	4	60	NA	NA

Ridebell ECII & ECS RIDE

10B	2	9	LINEAR	NA	1.0	4	4	40	NA	NA
-----	---	---	--------	----	-----	---	---	----	----	----

when used with y-cable in AUX inputs